

**PIT BOTTOM, RECALL DRIVE CONTROL UNITS
AND CAR TOP INSPECTION BOXES - GM Series**

GM406/EU

IP54



DESCRIPTION	SCHEME	CONTACT BLOCKS
Emergency stop EN ISO 13850 mushroom Ø 40 push-pull with vision:		Rated operating voltage Ue [V]: 690 Rated insulation voltage Ui [V]: 690 Rated impulse withstand voltage Uimp [kV]: 4 Rated thermal current Ith [A]: 16 Rated thermal current Ithe [A]: 16 Frequency [Hz]: 50/60 Rated operating current: AC 15 – DC 13
1 Schuko socket outlet 16A		
1 Cenelec socket outlet		GM407
1 USA socket outlet		GM408
1 Swiss socket outlet		GM408/SW
1 UK standard socket outlet		GM408/UK
1 Australia-China socket outlet		GM408/CH

GM403A

IP54



DESCRIPTION	SCHEME	CONTACT BLOCKS
Emergency stop EN ISO 13850 mushroom Ø 40 push-pull with vision:		Rated operating voltage Ue [V]: 690 Rated insulation voltage Ui [V]: 690 Rated impulse withstand voltage Uimp [kV]: 4 Rated thermal current Ith [A]: 16 Rated thermal current Ithe [A]: 16 Frequency [Hz]: 50/60 Rated operating current: AC 15 – DC 13
1 knob selector 0 - 1 to 90°		
1 Schuko socket outlet 16A		
1 Cenelec socket outlet		GM403/FR
1 USA socket outlet		GM403/US
1 Swiss socket outlet		GM403/SW
1 UK standard socket outlet		GM403/UK
1 Australia-China socket outlet		GM403/CH

GM401

IP54



DESCRIPTION	SCHEME	CONTACT BLOCKS
Emergency stop EN ISO 13850 mushroom Ø 40 push-pull with vision:		Rated operating voltage Ue [V]: 690 Rated insulation voltage Ui [V]: 690 Rated impulse withstand voltage Uimp [kV]: 4 Rated thermal current Ith [A]: 16 Rated thermal current Ithe [A]: 16 Frequency [Hz]: 50/60 Rated operating current: AC 15 – DC 13
1 Alarm push button - 1NO		
1 Schuko socket outlet 16A		
1 Cenelec socket outlet		GM401/FR
1 USA socket outlet		GM401/US
1 Swiss socket outlet		GM401/SW
1 UK standard socket outlet		GM401/UK
1 Australia-China socket outlet		GM401/CH

GM421

IP54



DESCRIPTION	SCHEME	CONTACT BLOCKS
Emergency stop EN ISO 13850 mushroom Ø 40 push-pull with vision:		Rated operating voltage Ue [V]: 690 Rated insulation voltage Ui [V]: 690 Rated impulse withstand voltage Uimp [kV]: 4 Rated thermal current Ith [A]: 16 Rated thermal current Ithe [A]: 16 Frequency [Hz]: 50/60 Rated operating current: AC 15 – DC 13
1 Alarm lighted push button - 1 NO		
1 Cenelec socket outlet		
1 Schuko socket outlet 16A		GM421/EU
1 USA socket outlet		GM421/US
1 Swiss socket outlet		GM421/SW
1 UK standard socket outlet		GM421/UK
1 Australia-China socket outlet		GM421/CH

PIT BOTTOM, RECALL DRIVE CONTROL UNITS AND CAR TOP INSPECTION BOXES - GM Series



GM491

IP54


DESCRIPTION

Emergency stop EN ISO 13850 mushroom Ø 40 push-pull with vision:

1 dual push button Alarm - Light 1NO+1NO

- 1 Schuko socket outlet 16A
- 1 Cenelec socket outlet
- 1 USA socket outlet
- 1 Swiss socket outlet
- 1 UK standard socket outlet
- 1 Australia-China socket outlet

SCHEME



CONTACT BLOCKS

Rated operating voltage Ue [V]: 690
 Rated insulation voltage Ui [V]: 690
 Rated impulse withstand voltage Uimp [kV]: 4
 Rated thermal current Ith [A]: 16
 Rated thermal current in enclosure Ithe [A]: 16
 Frequency [Hz]: 50/60
 Rated operating current: AC 15 – DC 13

GM492

GM492/US

GM492/SW

GM492/UK

GM492/CH



GM419

IP65

DESCRIPTION

Buzzer AC/DC 12-24V with:

- 1 Red led Light
- 1 Green led light

SCHEME



GM219

IP65

DESCRIPTION

Advising LED lights AC/DC 12-24V with:

- 1 Green led Light
- 1 Red led light

SCHEME



GM092BYPASS

IP65

DESCRIPTION

Landing and car door bypass device

Cam switch 1 - 2

SCHEME



CAM SWITCHES

Rated operating voltage Ue [V]: 690
 Rated insulation voltage Ui [V]: 690
 Rated impulse withstand voltage Uimp [kV]: 4
 Rated thermal current Ith [A]: 20
 Rated thermal current in enclosure Ithe [A]: 16
 Frequency [Hz]: 50/60



GM243

IP54

DESCRIPTION

Cam switch 0-1 90° switching with:

1 Schuko socket outlet 16A

SCHEME



CAM SWITCHES

Rated operating voltage Ue [V]: 690
 Rated insulation voltage Ui [V]: 690
 Rated impulse withstand voltage Uimp [kV]: 4
 Rated thermal current Ith [A]: 20
 Rated thermal current in enclosure Ithe [A]: 16
 Frequency [Hz]: 50/60

1 Cenelec socket outlet

1 USA socket outlet

1 Swiss socket outlet

1 UK standard socket outlet

1 Australia-China socket outlet



GM243/FR

GM243/US

GM243/SW

GM243/UK

GM243/CH

